

Single - Player Hanabi



not as boring as you'd think !

Cards

$$v = \# \text{ values}$$

$$c = \# \text{ colors}$$

a single card $\rightsquigarrow (p, q)$

↑
value

Color



The Single-Player version

Given : a stream of N cards .

The Single-Player Version

Given : a stream of N cards .

(identical cards might repeat up to r times)

The Single-Player Version

Given : a stream of N cards .

(identical cards might repeat up to r times)

Moves : Discard, Play, Store

can play (p, q) iff

the last card of color q played had value $p-1$

or $p=1$ & no cards of color q have been played.

The Single-Player version

Given : a stream of N cards .

(identical cards might repeat up to r times)

Moves : Discard, Play, Store

Win :

The Single-Player Version

Given : a stream of N cards .

(identical cards might repeat up to r times)

Moves : Discard, Play, Store

Win : If you can make stacks $1 \dots g$

for all colors c

The Single-Player Version

Given : a stream of N cards .

(identical cards might repeat up to r times)

Moves : Discard, Play, Store

Win : If you can make stacks $1 \dots g$





for all colors c

while Storing $\leq h$ cards @ all times

$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.





$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.




$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.




$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.




$r=2$, $h=2$



$N=12$; $\vartheta=3$, $c=3$

Example Run.

$r=2$, $h=2$



Special Cases

$$r = 1$$



no repeats.

What is the smallest holding threshold with which we can win?

holding threshold

h

Special Cases

$$r = 1$$



no repeats.

What is the smallest holding threshold with which we can win?

holding threshold

h

Natural strategy: play a card as early as you can.

Special Cases

$$r = 1$$



no repeats.

What is the smallest holding threshold with which we can win?

holding threshold
 h

Natural strategy: play a card as early as you can.

Q1. How much holding power do you need for this to work?

Special Cases

$$r = 1$$



no repeats.

What is the smallest holding threshold with which we can win?


 h

Natural strategy: play a card as early as you can.

Q2. Can you do better?

3

1

6


4

8


2

7


5




Draw an interval from every card to
its rightmost card w/ same color
but smaller value




Draw an interval from every card to
its rightmost card w/ same color
but smaller value




Draw an interval from every card to
its rightmost card w/ same color
but smaller value




Draw an interval from every card to
its rightmost card w/ same color
but smaller value




Draw an interval from every card to
its rightmost card w/ same color
but smaller value



Draw an interval from every card to
its rightmost card w/ same color
but smaller value




Draw an interval from every card to
its rightmost card w/ same color
but smaller value



Bubble Sort

One left - to - right pass :


Swap adjacent cards if they are
"out of order"



Bubble Sort

One left - to - right pass :


Swap adjacent cards if they are
"out of order"



Bubble Sort

One left - to - right pass :

Swap adjacent cards if they are
"out of order"




Bubble Sort

One left - to - right pass :

Swap adjacent cards if they are

"out of order"




Bubble Sort

One left - to - right pass :

Swap adjacent cards if they are


"out of order"



Bubble Sort

One left - to - right pass :

Swap adjacent cards if they are
"out of order"



Exercise

Bubble sort

passes = $\cancel{h_{opt}}$

Bubble Sort

One left - to - right pass :

Swap adjacent cards if they are
"out of order"

Special Cases

$c = 1$



one color

Special Cases

$c = 1$



one color

LAZY approach : play a card as late as possible .

Special Cases

$c = 1$



one color

LAZY approach : play a card as late as possible .

Store the LAST PLAYABLE INDEX for each value .

Special Cases

$$c = 1$$



one color

For any $i \in N$, we say that the $\underbrace{i^{\text{th}} \text{ card}}$ is ~~useless~~
Value: a_i

if $\exists w_1, \dots, w_{n+1} \in N$ s.t.

- $a_i < w_1 < \dots < w_{n+1} \leq v$
- $\forall j \in \{i+1, \dots, N\}$, it holds that $a_j \notin \{w_1, \dots, w_{n+1}\}$

Special Cases

$$c = 1$$



one color

For any $i \leq N$, we say that the $\underbrace{i^{\text{th}} \text{ card}}$ is ~~useless~~
Value: a_i

there exist $\geq h+1$ values higher than a_i ,

none of which appears after the i^{th} card in σ .

Special Cases

$$c = 1$$



one color

For any $i \leq N$, we say that the $\underbrace{i^{\text{th}} \text{ card}}$ is ~~useless~~
Value: a_i

there exist $\geq h+1$ values higher than a_i ,

none of which appears after the i^{th} card in σ .

Why?

Claim. Useless cards are never played in a winning sequence.

Special Cases

$c = 1$



one color

Idea

- ① Filter out the useless cards (how?)

Special Cases

$c = 1$

c

one color

Idea

- ① Filter out the useless cards (how?)
- ② Among the rest:

Special Cases

$c = 1$



one color

Idea

① Filter out the useless cards (how?)

② Among the rest:

ignore all cards except the one

which is the last card of a given value in T^*

Special Cases

$c = 1$



one color

Idea

① Filter out the useless cards (how?)

② Among the rest:

ignore all cards except the one

which is the last card of a given value in Γ^*

can play?

Special Cases

$c = 1$



one color

Idea

① Filter out the useless cards (how?)

② Among the rest:

ignore all cards **except** the one

which is the **last card** of a given value in Γ^*

can play?



Special Cases

$c = 1$



one color

Idea

① Filter out the useless cards (how?)

② Among the rest:

ignore all cards **except** the one

which is the **last card** of a given value in Γ^*

can play?

play

yes

Store

no

Special Cases

$c = 1$



one color

Idea


① Filter out the useless cards (how?)

② Among the rest:

ignore all cards **except** the one

which is the **last card** of a given value in Γ^*

★ also play all the
other playable cards



Special Cases

$c = 1$



one color

Claim. If the filtering phase knocks out ALL cards
of a given value, there is NO WIN.

Otherwise, the lazy algorithm actually works.

